









THIS DOCUMENT AND THE INFORMATION IT CONTAINS IS THE PROPERTY OF EMTEQ INC. AND MAY NOT BE USED IN ANY WAY WITHOUT THE EXPRESS WRITTEN CONSENT OF EMTEQ INC.

REV	REVISION	DATE	ER #	INTL
B	UPDATED NOTE 1	12/20/2006	6195	VML

NOTES:

- 1.) TERMINATE CONNECTOR USING EMTEQ CRIMPING INSTRUCTION, ES-106-1.
- 2.) PLUG KIT CONSISTS OF:  
PRE-INSERTED PLUG HOUSING & SHIELD  
MANAGEMENT BAR  
REAR HOUSING  
FERRULE
- 3.) MATERIALS:  
FRONT HOUSING PLASTIC:  
CLEAR POLYCARBONATE, UL 94-V0  
MANAGEMENT BAR:  
CLEAR POLYCARBONATE, UL 94-V0  
REAR HOUSING PLASTIC:  
BLACK POLYCARBONATE, UL 94-V0  
SHIELD:  
TIN PLATED BRASS  
CONTACTS:  
PHOSPHOR BRONZE,  
SELECTIVE GOLD PLATING  
FERRULE:  
TIN PLATED BRASS
- 4.) CONTACTS TERMINATE SOLID OR STRANDED CONDUCTORS BETWEEN 0.037 [0.94 mm] TO 0.042 [1.07 mm] OUTSIDE DIAMETER OF INSULATION.
- 5.) PLUG SPECIFICATION: FOR CATEGORY 5 APPLICATIONS.
- 6.) TOLERANCES COMPLY WITH F.C.C. DIMENSION REQUIREMENTS
7.  TERMINATED PLUG HEIGHT: 0.237 [6.02 mm] ± 0.005 [0.13 mm]



MATERIAL	SCALE	SIZE A	DATE 9/3/2004	 5349 S. EMMER DRIVE NEW BERLIN, WI 53151 (888) 679-6170
	FINISH	TOLERANCES UNLESS NOTED .XX = ± .03 .XXX = ± .010 ANGLES ± 1°		
CAD GENERATED AND MAINTAINED DRAWING -- DO NOT SCALE		APPROVED	CAGE CODE 06WH3	8 CONDUCTOR MODULAR PLUG, SHIELDED VERSION DWG # RJ45-0824FP SHT 1 OF 1
NOTICE -- ALL CHANGES TO THIS DOCUMENT ARE CONTROLLED BY EMTEQ INC / UNLESS OTHERWISE STATED, ALL REPRODUCTIONS OF THIS DOCUMENT ARE NOT CONTROLLED BY EMTEQ INC				

FILE: RJ45-0824FP.prt